



Lexmark™

Forms and Bar Code Card P4.2

User's Guide

June 2016

www.lexmark.com

Contents

- Overview..... 4**
 - Supported printer models.....4
- Supported fonts and bar codes..... 5**
 - Supported bar codes..... 5
 - Supported fonts.....9
- SAP support..... 11**
 - Installing SAP device types.....11
 - Modifying device types format and default settings..... 11
- Using Visual Bar Code Designer..... 12**
 - Supported Microsoft® Windows® operating systems..... 12
 - Installing Visual Bar Code Designer.....12
 - Generating bar code data.....12
- Creating and managing forms..... 13**
 - Forms overview.....13
 - Forms Card menu.....13
 - Bar code menu.....15
 - Storing forms on the printer..... 15
 - Capturing raw data for mapping..... 16
 - Printing forms from a flash drive..... 16
 - Identifying the version of forms on Forms and Bar Code Card..... 16
 - Font limitations..... 17
- Troubleshooting..... 18**
 - The printer does not respond after installation.....18
 - Forms Manager cannot detect the printer.....18
 - International fonts do not print as expected..... 18
 - Mismatched fonts in Forms Composer and on printed forms.....19
 - Form did not merge.....20
 - Form is printed in plain text.....20
 - Cannot fax or e-mail merged output.....20
 - Characters appear as boxes in PDFs viewed with Acrobat Reader..... 20

Cannot see complete list of supported forms..... 21
Data filters are not working..... 21
Cannot add new forms.....21
Bar codes do not print as expected.....21
Cannot generate bar codes using PCL emulation print drivers..... 22
Unexpected results after printing a bar code.....22
Printed bar code is unreadable..... 22

Notices..... 23

Edition notice.....23

Index..... 27

Overview

Lexmark™ Forms and Bar Code Card lets you print various standard forms and bar codes. Using an algorithm, Forms and Bar Code Card can generate bar codes in either PCL® 5 or PostScript® (PS) emulations.

With PCL 5 emulation, a printer with an installed card is the functional equivalent of HP BarCodes and More font set. It is also a compatible alternative to an HP LaserJet with HP BarDIMM Pro version 3.3a, including the FREESCAPE alternate escape code feature, and Intelligent Mail bar code. Forms and Bar Code Card also provides custom device types for printing with SAPscript in SAP R/3 applications.

Bar code options include the following features:

- OCR-A and OCR-B as bitmap and scalable fonts
- Independently scalable bar heights and widths
- RFID support
- Text embedment with selectable positioning
- Data format verification, with error reporting
- Automatic bar code data compression, when required
- Automatic bar code checksum calculation and character placement, when required
- Automatic placement of special characters, when required
- Built-in 256MB flash memory

Forms options include the following features:

- Storing and printing of forms from a 256MB flash memory or printer hard disk
- Built-in RFID support
- Creation of electronic forms to be merged with data
- Sending of merged output through fax and e-mail

Notes:

- Forms Composer and Forms Manager are required in creating and managing forms.
- The forms files on Forms and Bar Code Card have the file extensions .lfm and .lff.
- For more information on using RFID when printing forms, see the help documentation for Forms Composer.

Supported printer models

- Lexmark CS720, CS725, CS727de, CS728de
- Lexmark CS820, CS827de
- Lexmark CS921, CS923
- Lexmark CX725, CX727de
- Lexmark CX820, CX825, CX827de, CX860
- Lexmark CX920, CX921, CX922, CX923, CX924

Supported fonts and bar codes

Supported bar codes

One-dimensional bar code types and their availability on Forms and Bar Code Card

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
Australia Post 4-State bar code (37-CUST)	✓	✓
Australia Post 4-State bar code (52-FF-MET)	✓	✓
Australia Post 4-State bar code (67-FF-MET)	✓	✓
British Royal Mail 4-State customer code symbol (RM4SCC)	✓	✓
Codabar (USD -4, NW -7, Monarch, Code 2 of 7)	✓	✓
Codabar with mod16 check digit	✓	✓
Code 128 autoswitch	✓	✓
Code 128 A	✓	✓
Code 128 B	✓	✓
Code 128 C	✓	✓
Code 3 of 9	✓	✓
Code 3 of 9 with check digit	✓	✓
Code 3 of 9 extended	✓	✓
Code 3 of 9 extended with check digit	✓	✓
Code 3 of 9 space encoding	✓	x
Code 3 of 9 space encoding with check digit	✓	x
Code 93	✓	✓
Code 93 extended	✓	✓
Danish PTT 3 of 9	✓	✓
Dutch Post 4-State bar code	✓	✓
EAN/JAN-8	✓	✓
EAN/JAN-8 with 2-digit supplemental	✓	✓
EAN/JAN-8 with 5-digit supplemental	✓	✓
EAN/JAN-13	✓	✓

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
EAN/JAN-13 with 2-digit supplemental	✓	✓
EAN/JAN-13 with 5-digit supplemental	✓	✓
EAN 128	✓	✓
French Postal 3 of 9 A/R	✓	✓
German Postal 2 of 5 Leitcode	✓	✓
German Postal 2 of 5 Identcode	✓	✓
HIBC 39/128	✓	✓
Interleaved 2 of 5	✓	✓
Interleaved 2 of 5 with check digit	✓	✓
Intelligent Mail	✓	✓
Industrial 2 of 5	✓	✓
Industrial 2 of 5 with check digit	✓	✓
ISBN	✓	✓
ISBN+5	✓	x
ISSN	✓	✓
ISSN+2	✓	x
ISSN+5	✓	x
ITF-14	✓	x
Japan Post 4-State bar code	✓	✓
Matrix 2 of 5	✓	✓
Matrix 2 of 5 with check digit	✓	✓
MSI	✓	✓
MSI with mod10 check digit	✓	✓
MSI with mod10 and mod10 check digit	✓	✓
MSI with mod11 and mod10 check digit	✓	✓
Singapore Post 4-State bar code	✓	✓
Swiss Post	✓	✓
UCC 128	✓	✓
UPC-A	✓	✓
UPC-E	✓	✓
UPC-A with 2-digit supplemental	✓	✓

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
UPC-A with 5-digit supplemental	✓	✓
UPC-E with 2-digit supplemental	✓	✓
UPC-E with 5-digit supplemental	✓	✓
USPS PLANET bar code	✓	✓
USPS POSTNET 5-digit ZIP code	✓	✓
USPS POSTNET 9-digit ZIP with 4 code	✓	✓
USPS POSTNET 11-digit Delivery Point Code	✓	✓
USPS Expanded POSTNET	✓	x
USPS Tray label, 10-digit 2 of 5	✓	✓
USPS Sack label, 8-digit 2 of 5	✓	✓
USPS Zebra code	✓	✓
USPS FIM (Face Identification Marking)	✓	✓

Two-dimensional bar code types and their availability on Forms and Bar Code Card

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
Aztec	x	✓
Codablock F	✓	✓
Data Matrix	✓	✓
MaxiCode	✓	✓
MicroPDF417	✓	✓
PDF417	✓	✓
QR	✓	✓
RSS-14	✓	✓
RSS-14 Expanded	✓	✓
RSS-14 Limited	✓	✓
RSS-14 Stacked	✓	✓
RSS-14 Truncated	✓	✓

Composite bar code types and their availability on Forms and Bar Code Card

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
EAN-8	✓	✓
EAN/JAN-8 with 2-digit supplemental	✓	✓
EAN/JAN-8 with 5-digit supplemental	✓	✓
EAN-13	✓	✓
EAN/JAN-13 with 2-digit supplemental	✓	✓
EAN/JAN-13 with 5-digit supplemental	✓	✓
RSS-14	✓	✓
RSS-14 Expanded	✓	✓
RSS-14 Limited	✓	✓
RSS-14 Stacked	✓	✓
RSS-14 Truncated	✓	✓
UCC-128	✓	✓
UPC-A	✓	✓
UPC-E	✓	✓
UPC-A with 2-digit supplemental	✓	✓
UPC-A with 5-digit supplemental	✓	✓
UPC-E with 2-digit supplemental	✓	✓
UPC-E with 5-digit supplemental	✓	✓

Font-based bar code types and their availability on Forms and Bar Code Card

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
Code 128 bitmap regular	PCL only	x
Code 128 bitmap wide	PCL only	x
Code 128 scalable regular	PCL only	x
Code 128 scalable narrow	PCL only	x
Code 128 scalable wide	PCL only	x
Code 3 of 9 bitmap	PCL only	x
Code 3 of 9 scalable half inch regular	PCL only	x
Code 3 of 9 scalable one inch regular	PCL only	x
Code 3 of 9 quarter inch regular	PCL only	x

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
Code 3 of 9 small high regular	PCL only	x
Code 3 of 9 small low regular	PCL only	x
Code 3 of 9 small medium regular	PCL only	x
Code 3 of 9 slim regular	PCL only	x
Code 3 of 9 wide regular	PCL only	x
Interleaved 2 of 5 bitmap	PCL only	x
Interleaved 2 of 5 scalable regular	PCL only	x
Interleaved 2 of 5 scalable thin	PCL only	x
OCR-A	PCL only	x
OCR-B digits regular	PCL only	x
UPC tall	PCL only	x
UPC tall narrow	PCL only	x
UPC tall thin	PCL only	x
UPC half	PCL only	x
UPC half narrow	PCL only	x

Supported fonts

To obtain the PCL 5 escape sequences used to select these fonts, print the font list using the printer control panel. For more information, see the printer *User's Guide*.

Font	Type	Resides
Architext CMC7	Scalable	On the option card
CMC7	Scalable	On the option card
Code 3 of 9 (4.69)	Bitmap	On the option card
Code 3 of 9 (8.11)	Bitmap	On the option card
Electrical symbols	Scalable	On the option card
Euro and other currency symbols	Scalable	On the option card
Line Draw	Bitmap	On the option card
Manufacturing symbols	Scalable	On the option card
MICR	Scalable	On the option card
OCR-A	Bitmap	On the option card
OCR-A	Scalable	On the option card
OCR-B	Bitmap	On the option card
OCR-B	Scalable	On the option card

Font	Type	Resides
OCR-B in Bubbles	Scalable	On the option card
Roman Pillar	Scalable	On the option card
Roman Pillar Italic	Scalable	On the option card
Roman Pillar Bold	Scalable	On the option card
Roman Pillar Bold Italic	Scalable	On the option card
Roman Pillar5	Scalable	On the option card
UPC 10mil	Bitmap	On the option card
UPC 13mil	Bitmap	On the option card

SAP support

When used in PCL 5 emulation mode, SAP ERP software has built-in support for many of the functions provided by Forms and Bar Code Card.

For a list of supported device types, go to <http://service.sap.com>.

Installing SAP device types

Note: You must be the SAP Basis administrator to install SAP devices.

- 1 Start transaction SE38.
- 2 Execute report RSTXSCRIP to load the device type. For example, ZLXFORM2.
- 3 Type the name of the device type in the Object Name field.
Note: Do not include the .pri extension.
- 4 Select **IMPORT** mode, and then press the **F8** button (execute).
- 5 Reset the SAPscript cache:
 - a Call transaction SE38.
 - b Execute the report RSTXDELL, using `client = '*'`.
- 6 Reset the character code cache:
 - a Start transaction SP12.
 - b Click **character sets > Conf buffer (CCC) > Invalidate CCC**.

Note: The reset procedure is valid only on the actual instance, so you must connect on the instance where the spool work process is running.

- 7 Restart the spool work process:
 - a Highlight the spool work process SPO.
 - b Click **Process > cancel without core**.

Note: The spool work process automatically restarts after a few seconds or on the next interrupt.

Modifying device types format and default settings

- 1 Start transaction SPAD.
- 2 Click **Full Administration > Device Types**.
- 3 Double-click the device type.
- 4 Click **Format**, and then double-click the format you want to modify.
- 5 Click **Change**.
- 6 Double-click **Printer Initialization**, and then remove the number sign (#) from the beginning of each needed line.
- 7 Click **Save > Save**.

Using Visual Bar Code Designer

This application lets you select the bar code symbology and enter data to be encoded, and then prompt the software to generate the bar code.

Supported Microsoft® Windows® operating systems


- Windows 7
- Windows Vista®
- Windows XP
- Windows 2000
- Windows NT® 4.0
- Windows 98

Installing Visual Bar Code Designer

- 1 Insert the *Software and Documentation* CD.
- 2 From the Designer subdirectory, run **setup-vbd.exe**.
- 3 Review and accept the license agreement.
- 4 Select the folder where you want to install the application.
- 5 Follow the instructions on the computer screen.

Generating bar code data

Visual Bar Code Designer generates the PCL escape sequences, PCL HEX, or PostScript command sequences for bar codes. These data can be used within an application, SAP device type, or as a file to test print the bar code using Forms and Bar Code Card.

- 1 Click  or **Start**.
- 2 Click **Programs** or **All Programs**, and then select **Visual Bar Code Designer**.
- 3 Double-click the bar code symbology you want from the “Barcode list” window.
- 4 Modify the bar code settings if necessary.
- 5 From the Edit menu, copy the data stream you want, and then paste the text string in your application.

Notes:

- After the bar code data is generated, the test bar code can be printed by clicking the Print icon in the toolbar. The image of the bar code prints on any printer, including those without a Forms and Bar Code Card installed. The test bar code may be suitable for scanning.
- For more information, click the Visual Bar Code Designer Help menu, or see the *Forms and Bar Code Card Technical Reference Manual*.

Creating and managing forms

Forms overview

Electronic-forms solutions integrate both electronic and hard-copy documents, and let you create custom forms to create a dynamic document workflow for any business. The forms can be either printer based or server based. You can quickly design electronic forms, store them on a printer, or automatically merge them with text files, and then print, fax, e-mail, or archive the output.

The electronic-forms solutions contain different modules that automate workflow processes. These modules include Forms Composer and Forms Manager.

Forms Composer and Forms Manager

Note: Forms Composer and Forms Manager are required software programs that can be purchased separately.

Forms Composer is a design tool that offers the following features:

- Easy-to-use graphical user interface to create forms and map data to the forms
- Importing of existing PDF documents for compatibility
- Creation of documents for printer-based and server-based technologies

The Data pane of Forms Composer allows mapping variable data that comes from the host system. You can set the paper size and input text before downloading the form to the printer flash memory or printer hard disk. After a form is designed and is in the printer, data can be sent directly from your host computer over a TCP/IP network, through a USB connection to the printer, through a parallel card to the printer, or through a serial card to the printer. Forms and Bar Code Card then merges the data with the correct form using predefined activation conditions.

Activation conditions are defined as triggers that let you select the correct formset on the printer memory or printer hard disk. You can define activation conditions when designing your form in Forms Composer or creating a forms directive. Every time you create a new form for a data set, you are creating a project which you must upload to a printer with both flash memory and Forms and Bar Code Card installed.

Forms Manager downloads and manages formsets on printers where Forms and Bar Code Card is installed. You can add formsets to printers, retrieve printer information, and view saved files on the printer. Using Forms Manager, you can also upgrade the Forms and Bar Code Card firmware on the printer.

Forms and Bar Code Card has firmware that automatically merges the data with the correct form design (formset) and prints the completed form. The host data stream can be SAP RDI, ASCII, or double-byte data encoded in GBK, UTF-8, or UTF-16. Forms and Bar Code Card uses TrueType fonts and Adobe Font Manager (AFM) to generate PDF output.

Forms Card menu

After Forms and Bar Code Card is installed, more menu items are available. These menu items can be found in the Forms Card menu, which is available on the Embedded Web Server.

Merge Mode settings

- **Merge Mode**
 - **Print**—Print the merged output.
 - **Disabled**—Pass all received data to the printer. No attempt is made to merge data onto a formset.
 - **Data Capture**—Incoming data stream is written to a file on the printer storage device. This file can be used as a sample data file during formset creation.
 - **Archive and Print**—Merged PDF files are printed and archived in the formsmerge or archive directory. This option is available only when the printer hard disk is installed and Forms and Bar Code Card is configured to use the printer hard disk for formsets.
 - **Archive only**—Merged PDF files are only archived in the formsmerge or archive directory. This option is available only when the printer hard disk is installed and Forms and Bar Code Card is configured to use the printer hard disk for formsets.
- **Data Capture Target**—This option is available only when Data Capture is selected.
 - **Flash**
 - **Thumbdrive**—This option is available only when a flash drive is inserted into the printer. When using this feature, make sure that a formsmerge directory (case sensitive) exists in the flash drive.

Print Port and Filter settings

- **Network Port, USB Port, Parallel Port, or Serial Port**—Select to use the formsmerge code to process all data sent to the network, USB, parallel or serial port. Otherwise, the data file is printed as determined by the basic printer language setting.
- **Network Filter, USB Filter, Parallel Filter, or Serial Filter**—Select whether to run incoming forms jobs through the selected filter before Forms and Bar Code Card processes it.

Note: Parallel Filter and Serial Filter is only available depending on your printer model.

List of filter options:

Note: Some options may not be available depending on your printer model.

- **Disabled**—Indicate that all data filters are off.
- **NULL**—Remove all null characters.
- **AS400**—Remove extraneous lines of data due to AS400 formatting.
- **PCL**—Remove all PCL escape sequences and leave plain text.
- **ZPL**—Remove Zebra Programming Language (ZPL) directives.
- **ZPL-F**—This value is the same as ZPL, except it uses “@” as the escape character instead of “^.”
- **OFIS**—Remove all Optra Forms™ initialization strings.
- **OFIS+NULL**—Remove all null characters and all Optra Forms initialization strings.
- **AS400+OFIS**—Remove extraneous lines of data due to AS400 formatting and all Optra Forms initialization strings.
- **Local Port Timeout**—Allow users to select a timeout value from 1 to 100 for forms jobs that come in on any of the local ports. The default value is 10 seconds.

Notes:

- This setting does not apply to forms jobs sent to the network ports.

- When formsmerge is active on a local port, a job times out when triggered by the Local Port Timeout or the Printer Timeout—whichever is shorter. This activity terminates the current job as if an “End of Form” character has been reached.

Copy Formsets settings

Note: Make sure that a formsmerge directory (case sensitive) exists in the flash drive.

- **Copy Replace Duplicates**—Copy and replace existing formats of the same name from a flash drive.
- **Copy Do Not Replace**—Cannot copy formsets with duplicate names from a flash drive.

Miscellaneous settings

- **Print All Forms**—Print all formset information found on Forms and Bar Code Card.

Notes:

- If a .ppf file exists for the formset, then the paper tray and output bin information is read from the .ppf file and listed under the .ppf file name.
- If both a printer hard disk and a flash memory are installed, then both total size and available size for the flash memory are shown. Only the forms on the user flash are accessible.
- **Error Page Print**—Print an error page when Forms and Bar Code Card encounters an error.

Bar code menu

The bar code menu is also available on the Embedded Web Server.

- **Alt ESC Code**—A bar code function that allows the use of an alternate escape character when processing PCL escape sequences.
 - **On**—Uses an alternate escape code character in addition to the default escape code character.
 - **Off**—Uses the default escape code character.
- **ESC Character**—When Alt ESC Code is set to On, the value defined in this setting is used in addition to the default escape character.
 - 126 (^)
 - 34 (“)
 - 35 (#)
 - 36 (\$)
 - 47 (/)
 - 63 (?)
 - 92 (\)
 - 123 ({})
 - 124 (|)
 - 125 (})

Storing forms on the printer

To store forms on the printer, an optional flash memory or printer hard disk must be installed. When it is installed, use Forms Manager to interact with the optional flash memory or printer hard disk.

Use Forms Manager to do the following:

- Store forms on the flash memory or printer hard disk.
- Erase all forms from the flash memory or printer hard disk.
- View all forms currently stored on the printer.

Capturing raw data for mapping

Capturing raw data is necessary to properly map data to forms. For more information, see the help documentation for Forms Manager.

- 1** In Forms Manager, select your printer from the Printer list.
- 2** Click **Printer > Properties**.
- 3** From the Mode section of the Printer Properties dialog, select **Data Capture**, and then click **Apply**.
- 4** Send the data file to the printer.
- 5** Refresh the printer in Forms Manager.
To retrieve the data file, select it.

Printing forms from a flash drive

The Create Flash File option in Forms Manager is used to add one or more formsets to printers that are not attached to the network. The flash file allows Forms Manager to communicate with these printers. The flash file created contains everything needed to add the formsets to the printer. You can save the file to a flash drive and then access it through the USB port on the printer.

For more information on creating flash files, see the help documentation for Forms Manager.

Notes:

- If formsets on the flash drive, the printer memory, or the printer hard disk contain the same activation conditions, then the formsets on the flash drive are used when those conditions are met.
- This function is supported only on printers with a USB port.

Identifying the version of forms on Forms and Bar Code Card

Do either of the following:

- Print a menu settings page. The current version of forms is listed under Installed Features. For more information on printing a menu settings page, see the printer *User's Guide*.
- Select the printer in Forms Manager, and then view the printer properties.

Note: Forms Manager is also used when upgrading the Forms and Bar Code Card firmware.

Font limitations

Windows fonts often contain more characters than the installed printer fonts. As a result, the printer may not print all the characters on a form. This is usually a problem only for characters that fall outside of the 0–255 character code range for nonstandard code pages. Print a sample form to check whether all the characters you want are printed.

Troubleshooting

The printer does not respond after installation

Make sure that the option card is installed correctly

Turn the printer off, and then reinstall the option card. For more information, see the installation sheet that came with the Forms and Bar Code Card kit.

Forms Manager cannot detect the printer

Try one or more of the following:

Check printer connections

Make sure that:

- The printer is turned on.
- The power cord is plugged into the printer and into a properly grounded electrical outlet.
- The printer is not plugged into any surge protectors, uninterruptible power supplies, or extension cords.
- The printer is securely connected to the computer, print server, or other network access point.
- You have resolved any error messages on the printer control panel display.

Make sure that the printer is connected to the network

The printer must be on the network and must match the IP or DNS name of the network.

International fonts do not print as expected

The international font set on the client computer does not match the font set on Forms and Bar Code Card.

Switch to one of the fonts available on Forms and Bar Code Card

The following international fonts are recommended for forms printed on a printer with an installed Forms and Bar Code Card:

Intl-Univers
Intl-CG Times
Intl-Courier
ArialMT
Times New RomanPSMT

Mismatched fonts in Forms Composer and on printed forms

Try one or more of the following:

Make sure that Forms Composer and the printer are configured properly

Make sure that the workflow properties for the data stream have been properly configured. For more information, see the help documentation for Forms Composer.

For information on configuring network settings, see the documentation that came with the printer.

Check that font mapping has not been altered in Forms Composer

The fonts.dat file in the Forms Composer directory specifies which fonts are used for font families with nonstandard names. The format for the information contained in the fonts.dat file follows the convention **font name, regular, bold, italic, bold italic**. These entries specify which fonts Forms Composer uses under which circumstances.

For example, an entry for the Bookman font family in the fonts.dat file might read **Bookman, Bookman, Bookman Demi, Bookman Italic, Bookman Demi Italic**. In this example, Forms Composer uses the font Bookman Demi for all instances of Bookman in boldface

Note: The fonts.dat file only specifies usage for font families with nonstandard names. For example, Courier, which uses Courier, Courier Bold, Courier Italic, and Courier Bold Italic are not listed.

To check or alter the fonts.dat file:

- 1 From the Forms Composer directory, use a text editor to open **fonts.dat**.
- 2 Make necessary changes to the file.
- 3 Save the file as fonts.dat into the same directory.

Check that font mapping has not been altered on the printer

Forms and Bar Code Card relies on font mapping to specify which fonts are used under which circumstances. The information is contained in the manager.upr file that resides in the Forms Manager directory. When you add a printer to Forms Manager, the manager.upr file is written to it.

To check or alter the manager.upr file for a particular printer:

- 1 From the Forms Manager\Fonts directory, use a text editor to open **manager.upr**.
- 2 Make necessary changes to the file.
- 3 Save the file as manager.upr into the same directory, and then delete the manager.bak file.
- 4 From Forms Manager, delete the printer and its associated files, and then add the printer you just deleted.

Note: For more information on adding and deleting printers, see the help documentation for Forms Manager.

Use fonts in Forms Composer that match those on Forms and Bar Code Card

Install matching fonts on Forms and Bar Code Card

For more information on installing fonts, see the help documentation for Forms Manager.

Form did not merge

Remove unnecessary characters from the beginning of the form

A blank page prints because the first element on the page is the character for form feed or carriage return. Form feed or carriage return characters at the beginning of a data stream cause the printer to skip to the next page. As a result, the print job or page activation conditions may be missed.

Form is printed in plain text

Try one or more of the following:

Review the activation conditions in Forms Composer

Use Forms Composer to set up activation conditions for the form.

Make sure that the formsmerge function is not deactivated by Forms Manager

From Forms Manager, open the Printer Properties menu to activate formsmerge.

Cannot fax or e-mail merged output

Make sure that the workflow properties for the data stream are configured properly

For more information, see the help documentation for Forms Composer.

For information on configuring network settings, see the printer *User's Guide*.

Characters appear as boxes in PDFs viewed with Acrobat Reader

Acrobat Reader may not correctly display all characters in archived and e-mailed attachments.

Use a different program to view PDFs

Merged output and preview output should match exactly. If boxes appear instead of characters in PDFs, switching to a different PDF viewer (such as Foxit Reader, available from www.foxitsoftware.com) should solve the problem.

Cannot see complete list of supported forms

Use Forms Manager to view all forms stored on the optional flash memory card or the printer hard disk

Data filters are not working

Check the Data Filters menu to see if the filter that you want is enabled

Cannot add new forms

Try one or more of the following:

Delete unused forms

Defragment the flash memory

The flash memory may be full. You can access this feature from the Printer Properties in Forms Manager.

Bar codes do not print as expected

Try one or more of the following:

Make sure that the option card is compatible with the printer

Make sure that the option card is installed

- 1 Print a menu settings page.
- 2 In the Printer Information section, check that the Forms and Bar Code Card option is listed.

Note: For more information on printing a menu settings page, see the printer *User's Guide*.

When using a PCL 5 emulation print driver, make sure that the escape sequence used to generate the bar code is constructed properly

The escape sequence must begin with Esc and contain the #T parameter (not case sensitive) for the bar code to be generated. Default values are used for parameters not explicitly defined in the sequence.

Cannot generate bar codes using PCL emulation print drivers

The option card does not support bar code printing with PCL XL or HPGL/2 emulation print drivers. Only printing with PCL 5 is supported.

Disable advanced features using a PCL XL emulation printer driver

- 1 From a Windows-based application, open the Print Properties dialog.
- 2 Click the **Graphics** tab.
- 3 From the Graphic mode list, select **Auto select**.

Unexpected results after printing a bar code

Try one or more of the following:

Make sure that the PCL 5 emulation escape sequences are complete

Immediately follow the PCL 5 emulation escape sequences that generate bar codes with an escape sequence that specifies a normal text font. For example, ^{Esc}(**s0p12h0s0b4099T** returns the text to 12-pitch Courier with fixed pitch spacing immediately following the embedded bar code.

Make sure that all parameters needed are fully specified

Parameter values are not retained for subsequent bar code PCL 5 escape sequences. Each time a bar code is generated, fully specify all parameters needed for each bar code.

Default values are used for any unspecified parameters.

Printed bar code is unreadable

Make sure that Print Quality settings are not too dark or too light

Print Resolution and Toner Darkness settings can affect the quality of printed bar codes. From Print Properties, adjust the Print Quality settings before printing another bar code.

Check the paper

Use only paper that meets printer specifications. For more information, see the documentation that came with the printer.

Notices

Edition notice

June 2016

The following paragraph does not apply to any country where such provisions are inconsistent with local law: LEXMARK INTERNATIONAL, INC., PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This publication could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in later editions. Improvements or changes in the products or the programs described may be made at any time.

References in this publication to products, programs, or services do not imply that the manufacturer intends to make these available in all countries in which it operates. Any reference to a product, program, or service is not intended to state or imply that only that product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any existing intellectual property right may be used instead. Evaluation and verification of operation in conjunction with other products, programs, or services, except those expressly designated by the manufacturer, are the user's responsibility.

For Lexmark technical support, visit <http://support.lexmark.com>.

For information on supplies and downloads, visit www.lexmark.com.

© 2016 Lexmark International, Inc.

All rights reserved.

GOVERNMENT END USERS

The Software Program and any related documentation are "Commercial Items," as that term is defined in 48 C.F.R. 2.101, "Computer Software" and "Commercial Computer Software Documentation," as such terms are used in 48 C.F.R. 12.212 or 48 C.F.R. 227.7202, as applicable. Consistent with 48 C.F.R. 12.212 or 48 C.F.R. 227.7202-1 through 227.7207-4, as applicable, the Commercial Computer Software and Commercial Software Documentation are licensed to the U.S. Government end users (a) only as Commercial Items and (b) with only those rights as are granted to all other end users pursuant to the terms and conditions herein.

Trademarks

Lexmark, the Lexmark logo, and Optra Forms are trademarks or registered trademarks of Lexmark International, Inc. in the United States and/or other countries.

Microsoft, Windows, Windows Vista, and Windows NT are either registered trademarks or trademarks of the Microsoft group of companies in the United States and other countries.

PCL® is a registered trademark of the Hewlett-Packard Company. PCL is Hewlett-Packard Company's designation of a set of printer commands (language) and functions included in its printer products. This printer is intended to be compatible with the PCL language. This means the printer recognizes PCL commands used in various application programs, and that the printer emulates the functions corresponding to the commands.

PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. The following terms are trademarks or registered trademarks of these companies:

Arial	The Monotype Corporation plc
CG Times	Based on Times New Roman under license from The Monotype Corporation plc, is a product of Agfa Corporation
ITC Bookman	International Typeface Corporation
Times New Roman	The Monotype Corporation plc
TrueType	Apple Computer, Inc.
Univers	Linotype-Hell AG and/or its subsidiaries

All other trademarks are the property of their respective owners.

Notice to users in the European Union

This product is in conformity with the protection requirements of EC Council directives 2004/108/EC, 2006/95/EC and 2005/32/EC on the approximation and harmonization of the laws of the Member States relating to electromagnetic compatibility, safety of electrical equipment designed for use within certain voltage limits and the ecodesign of energy-using products.

Compliance is indicated by the CE marking.



The manufacturer of this product is: Lexmark International, Inc., 740 West New Circle Road, Lexington, KY, 40550 USA. The authorized representative is: Lexmark International Technology Hungária Kft., 8 Lechner Ödön fasor, Millennium Tower III, 1095 Budapest HUNGARY, A declaration of conformity to the requirements of the Directives is available upon request from the Authorized Representative.

This product satisfies the Class B limits of EN 55022 and safety requirements of EN 60950.

Products equipped with 2.4GHz Wireless LAN option are in conformity with the protection requirements of EC Council directives 2004/108/EC, 2006/95/EC, and 1999/5/EC on the approximation and harmonization of the laws of the Member States relating to electromagnetic compatibility, safety of electrical equipment designed for use within certain voltage limits and on radio equipment and telecommunications terminal equipment.

Compliance is indicated by the CE marking.



Operation is allowed in all EU and EFTA countries, but is restricted to indoor use only.

The manufacturer of this product is: Lexmark International, Inc., 740 West New Circle Road, Lexington, KY, 40550 USA. The authorized representative is: Lexmark International Technology Hungária Kft., 8 Lechner Ödön fasor, Millennium Tower III, 1095 Budapest HUNGARY, A declaration of conformity to the requirements of the Directives is available upon request from the Authorized Representative.

European Community (EC) directives conformity

This product is in conformity with the protection requirements of EC Council directives 2014/30/EU, 2014/35/EU, 2009/125/EC, and 2011/65/EU on the approximation and harmonization of the laws of the Member States relating to electromagnetic compatibility, safety of electrical equipment designed for use within certain voltage limits, the ecodesign of energy-related products, and on the restrictions of use of certain hazardous substances in electrical and electronic equipment.

The manufacturer of this product is: Lexmark International, Inc., 740 West New Circle Road, Lexington, KY, 40550 USA. The authorized representative is: Lexmark International Technology Hungária Kft., 8 Lechner Ödön fasor, Millennium Tower III, 1095 Budapest HUNGARY. A declaration of conformity to the requirements of the Directives is available upon request from the Authorized Representative or may be obtained at www.lexmark.com/en_us/about/regulatory-compliance/european-union-declaration-of-conformity.html.

This product satisfies the Class B limits of EN 55022 and EN55032 and safety requirements of EN 60950-1 or EN 62368-1.

This product may be used in the countries indicated in the table below.

AT	BE	BG	CH	CY	CZ	DE	DK	EE
EL	ES	FI	FR	HR	HU	IE	IS	IT
LI	LT	LU	LV	MT	NL	NO	PL	PT
RO	SE	SI	SK	TR	UK			

Česky	Společnost Lexmark International, Inc. tímto prohlašuje, že výrobek tento výrobek je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 1999/5/ES.
Dansk	Lexmark International, Inc. erklærer herved, at dette produkt overholder de væsentlige krav og øvrige relevante krav i direktiv 1999/5/EF.
Deutsch	Hiermit erklärt Lexmark International, Inc., dass sich das Gerät dieses Gerät in Übereinstimmung mit den grundlegenden Anforderungen und den übrigen einschlägigen Bestimmungen der Richtlinie 1999/5/EG befindet.
Ελληνική	ΜΕ ΤΗΝ ΠΑΡΟΥΣΑ Η LEXMARK INTERNATIONAL, INC. ΔΗΛΩΝΕΙ ΟΤΙ ΑΥΤΟ ΤΟ ΠΡΟΪΟΝ ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 1999/5/ΕΚ.
English	Hereby, Lexmark International, Inc., declares that this type of equipment is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.
Español	Por medio de la presente, Lexmark International, Inc. declara que este producto cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o exigibles de la Directiva 1999/5/CE.
Eesti	Käesolevaga kinnitab Lexmark International, Inc., et seade see toode vastab direktiivi 1999/5/EÜ põhinõuetele ja nimetatud direktiivist tulenevatele muudele asjakohastele sätetele.
Suomi	Lexmark International, Inc. vakuuttaa täten, että tämä tuote on direktiivin 1999/5/EY oleellisten vaatimusten ja muiden sitä koskevien direktiivin ehtojen mukainen.
Français	Par la présente, Lexmark International, Inc. déclare que l'appareil ce produit est conforme aux exigences fondamentales et autres dispositions pertinentes de la directive 1999/5/CE.
Magyar	Alulírott, Lexmark International, Inc. nyilatkozom, hogy a termék megfelel a vonatkozó alapvető követelményeknek és az 1999/5/EC irányelv egyéb előírásainak.

Íslenska	Hér með lýsir Lexmark International, Inc. yfir því að þessi vara er í samræmi við grunnkröfur og aðrar kröfur, sem gerðar eru í tilskipun 1999/5/EC.
Italiano	Con la presente Lexmark International, Inc. dichiara che questo prodotto è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 1999/5/CE.
Latviski	Ar šo Lexmark International, Inc. deklarē, ka šis izstrādājums atbilst Direktīvas 1999/5/EK būtiskajām prasībām un citiem ar to saistītajiem noteikumiem.
Lietuvių	Šiuo Lexmark International, Inc. deklaruoja, kad šis produktas atitinka esminius reikalavimus ir kitas 1999/5/EB direktyvos nuostatas.
Malti	Bil-preżenti, Lexmark International, Inc., jiddikjara li dan il-prodott huwa konformi mal-ħtiġijiet essenzjali u ma dispożizzjonijiet oħrajn relevanti li jinsabu fid-Direttiva 1999/5/KE.
Nederlands	Hierbij verklaart Lexmark International, Inc. dat het toestel dit product in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 1999/5/EG.
Norsk	Lexmark International, Inc. erklærer herved at dette produktet er i samsvar med de grunnleggende krav og øvrige relevante krav i direktiv 1999/5/EF.
Polski	Niniejszym Lexmark International, Inc. oświadcza, że niniejszy produkt jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 1999/5/EC.
Português	A Lexmark International Inc. declara que este produto está conforme com os requisitos essenciais e outras disposições da Diretiva 1999/5/CE.
Slovensky	Lexmark International, Inc. týmto vyhlasuje, že tento produkt spĺňa základné požiadavky a všetky príslušné ustanovenia smernice 1999/5/ES.
Slovensko	Lexmark International, Inc. izjavlja, da je ta izdelek v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 1999/5/ES.
Svenska	Härmed intygar Lexmark International, Inc. att denna produkt står i överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 1999/5/EG.

Index

B

- bar code
 - generating data 12
 - generating, troubleshooting 22
- bar code menu
 - alternate escape character 15
 - escape character 15
- bar code options features 4
- bar codes
 - composite 5
 - font-based 5
 - one-dimensional 5
 - supported 5
 - two-dimensional 5
- bar codes do not print as expected 21

C

- cannot add new forms 21
- cannot fax or e-mail merged output 20
- cannot generate bar codes using PCL emulation printer drivers 22
- cannot see complete list of supported forms 21
- capturing raw data for mapping 16
- characters appear as boxes in PDFs viewed with Acrobat Reader 20

D

- data filters are not working 21
- data mapping
 - capturing raw data 16

E

- emission notices 24

F

- flash drive
 - printing forms from 16
- flash memory is full 21
- font limitations 17
- fonts
 - limitations 17

- mismatch in Forms Composer and printed forms 19
- supported 9
- form did not merge 20
- form is printed in plain text 20
- forms
 - identifying version 16
 - printing from a flash drive 16
 - storing 15

- Forms and Bar Code Card
 - identifying forms version 16

- Forms Card menu
 - copy formset 13
 - error page print 13
 - local port timeout 13
 - merge mode 13
 - network filters 13
 - network port 13
 - print all forms 13
 - USB filters 13
 - USB port 13

- Forms Composer
 - font mismatch, troubleshooting 19
 - overview 13

- Forms Manager
 - cannot detect printer, troubleshooting 18
 - capturing raw data for mapping 16
 - overview 13
 - setting printer to Data Capture mode 16

- Forms Manager cannot detect the printer 18
- forms options features 4
- forms overview 13

G

- generating bar code data 12

I

- installing SAP device types 11
- installing Visual Bar Code Designer 12
- international fonts do not print as expected 18

M

- menu
 - bar code 15
 - Forms Card 13
- merged output
 - cannot fax or e-mail, troubleshooting 20
- mismatched fonts in Forms Composer and on printed forms 19
- modifying device types format and default settings 11

N

- notices 24, 25

O

- options features
 - bar codes 4
 - forms 4
- overview
 - forms 13
 - Forms and Bar Code Card 4
 - Forms Composer 13
 - Forms Manager 13

P

- PDFs
 - problems with 20
- printed bar code is unreadable 22
- printer does not respond after installation 18
- printer models
 - supported 4
- printing forms from a flash drive 16

S

- SAP
 - installing device types 11
- SAP device types
 - installing 11
 - modifying format 11
 - modifying settings 11
- storing forms on the printer 15
- supported bar codes 5

supported operating systems 12
supported printer models 4

T

troubleshooting

- bar codes do not print as expected 21
- cannot add new forms 21
- cannot fax or e-mail merged output 20
- cannot generate bar code using PCL emulation printer drivers 22
- cannot see complete list of supported forms 21
- data filters are not working 21
- flash memory is full 21
- form did not merge 20
- form is printed in plain text 20
- Forms Manager cannot detect printer 18
- international fonts do not print as expected 18
- printed bar code is unreadable 22
- printer does not respond after installation 18
- unexpected results after printing a bar code 22

U

unexpected results after printing a bar code 22

V

Visual Bar Code Designer

- generating bar code data 12
- installing 12
- supported operating systems 12