

מדריך לפגמים בהדפסה

מדידות פגמים חוזרים

התאם מערכת של פגמי הדפסה חוזרים במשימת הדפסה לסימנים על אחד מהקווים האנכיים. הקו המתאים ביותר לפגמים במשימת ההדפסה מציין איזה חלק מסוים גורם לפגם.

הערה: קיימים ארבעה דפי צבע נוספים ודף ריק אשר יודפסו עם הדפסת מדריך זה. השתמש בדפים אלה לסיוע במציאת החלק הפגום.

החלף את ה-fuser אם אחד מהפגמים החוזרים האלה מופיע על הדף המודפס.

החלף את מחסנית הטונר של הצבע המתאים לפגם זה.

החלף את יחידת הפוטוקונדוקטור של הצבע המתאים לפגם זה.

113 מ"מ
(4.45 אינץ')

94.8 מ"מ
(3.73 אינץ')

47.4 מ"מ
(1.87 אינץ')

35.3 מ"מ
(1.39 אינץ')

33.0 מ"מ
(1.30 אינץ')

28.3 מ"מ
(1.11 אינץ')

72.4 מ"מ
(2.85 אינץ')

The diagram consists of seven vertical rectangles arranged horizontally. Each rectangle has a horizontal line segment extending from its right side at a specific height. The heights of these segments, from left to right, are: 1. A short segment near the bottom. 2. A segment slightly higher than the first. 3. A segment at the top of the rectangle. 4. A segment at the top of the rectangle. 5. A segment at the top of the rectangle. 6. A segment at the top of the rectangle. 7. A segment at the top of the rectangle. The rectangles are labeled 1 through 7 from left to right.



